

(주) DH케미칼

326 Hwasan-ri, Onsan-eub, Ulju-kun, Ulsan 689-896
Republic of Korea
TEL : 82-52-239-2163
FAX : 82-52-239-2151



CERTIFICATE OF ANALYSIS

PRODUCT NAME : MAGNATEC HYBRID 0W-20

MANUFACTURED DATE : 29 April 2024

LOT NO : DE2903K

REPORTED DATE : 29 April 2024

<u>ITEM</u>	<u>METHOD</u>	<u>SPECIFICATION</u>	<u>RESULT</u>
APPEARANCE (Conc.)	Visual	Clear & Bright	Clear & Bright
DENSITY (at 15 °C, g/cm ³)	ASTM D4052	Typ.0.8448	0.8446
Viscosity, Kinematic 100 °C	ASTM D445	8.0 - 9.0	8.564
Viscosity, CCS -35 °C (0W)	ASTM D5293	Max.6100	5920
POUR POINT(°C)	ASTM D97	Max.-39	-42
CALCIUM (wt%)	ASTM D4951	0.091 - 0.106	0.0929
ZINC (wt%)	ASTM D4951	0.078 - 0.093	0.0813
FOAM (SEQUENCE II, Tendency)	ASTM D892	Max.50	10
FOAM (SEQUENCE II, Stability)	ASTM D892	Max.0	0

Certified that the product described conform to the relevant specifications and that above data was obtained from tests conducted in accordance with the quality assurance procedures of DH Chem Co. Ltd. This Certificate is computerized and therefore not signed.

K.H.Choi
R&D Manager